



COMPANY WITH QUALITY MANAGEMENT
SYSTEM CERTIFIED BY DNV
= ISO 9001:2008 =

Heavy Duty Truck Lifts



Reliable and safe
mechanical screw
type design



MOBILE COLUMN LIFTS

Available in sizes from 7,000 lbs up to 22,000 lbs per column.

RAV 242

Four column set of 16,000 lbs. each.
System can be operated from any post.

RAV 262

Four column set of 18,000 lbs. each.
System can be operated from any post.


RAV 272

Four column set of 22,000 lbs. each.
System can be operated from any post.

RAV 242	4 x 16,000 lbs
RAV 262	4 x 19,000 lbs
RAV 272	4 x 22,000 lbs



AXLE HEIGHT SELECTION




Possibility of setting a different height between pairs of columns while retaining the subsequent control level synchronization.

MODULAR

1 x 8



2 x 4



Modular electrical systems enable alterations to be made to configuration (e. g. passing 4 to 6 to 8 columns, or creating two sets of 4 columns by splitting a set of 8).




240 series
Mechanical
towing jack



260-270 series
Hydraulic towing jack



240-260 SERIES
Lifting unit.



240-260 SERIES
Motor gear unit,
obstacle or main
nut wear safeties.

RAV
212
222
232
242
262
272



MOBILE COLUMN LIFTS

RAV 212

Four column set of 7,000 lbs. each.

RAV212N: controls only on master column.

RAV212NL: system can be operated from any post. Possibility to set pair of columns at different height.

RAV 222

Four column set of 9,000 lbs. each.

RAV222N: controls only on master column.

RAV222NL: system can be operated from any post. Possibility to set pair of columns at different height.

RAV 232

Four column set of 12,000 lbs. each.

RAV232N: controls only on master column.

RAV232NL: system can be operated from any post. Possibility to set pair of columns at different height.

RAV 212	4 x 7,000 lbs
RAV 222	4 x 9,000 lbs
RAV 232	4 x 12,000 lbs



210-220-230 series
Handle (1 per set)



STANDS

Adjustable stands allows vehicle to be safely supported while columns are used to lift another vehicle. Adjustable up to 70".

S260A1 - standard stand

S270A1 - equipped with support heads with screw adjustment

S270A2 - spring-loaded transportation wheels. Equipped with support heads with screw adjustment



H min.	S260A1 / 16,500 lbs	S270A1 / 22,000 lbs	S270A2 / 22,000 lbs
H max	52" 80"	48" 80"	48" 80"

OPTION



S260A10
15,000 lbs frame kit (2 units)



S 270 A3



S 270 A4 / 270 A8

ADAPTERS FOR WHEEL HAVING DIAMETER LESS THAN 35"

S 270 A3 - Ø 35" ÷ 31 1/2"

S 270 A4 - Ø 31 1/2" ÷ 27 1/2"

S 270 A8 - Ø 27 1/2" ÷ 19 1/2"



RAV AMERICA
800.816.8138
info@ravamerica.com
www.ravamerica.com

INTERNATIONAL

Ravaglioli S.p.A.
40037 Sasso Marconi
Fraz. Pontecchio M.
P.O.B. 1690 - Bologna - Italia
Tel. +39 - 051 - 6781511
Fax +39 - 051 - 846349
rav@ravaglioli.com
www.ravaglioli.com