

### Easy Demounting (upper bead)

Bead demount controls: down and up and the bead is demounted



Patented tool in plastic anti-scratch material

### Easy Demounting (lower bead)



Quick locking unit (standard)

Two position locking plate for standard or reverse rims

### Space Saver

Post with "space saver" vertical movement

### Tool Memory

Rim edge "memory" controls: place it first time, then it will go back to same position just pushing a pedal

Lever for quick opening of bead breaker arm




### Easy Bead Breaking

1 + 2 + 3



Roller rotation 180°



G800A26 - Bead-breaker adaptor with tilting adjustment

### 0-16 INVE MOTOR RPM VARIABLE SPEED


#### TECHNICAL DATA

Handled wheels from	10" - 26"
Max wheel diameter	45"/1143 mm
Max wheel width	381 mm (15")
Max side shovel bead loosener opening	432 mm (17")
Recommended air supply	8-10 bar / 115-145PSI
Rotation motor	1,5 Kw inv. + 0,75kw motor
Bead loosener power (roller)	1200 kg (2645 lbs)
Bead loosener power (side shovel)	3600 kg (7900 lbs)

G8945DS.ITA + G800A26

MEMORY

#### STANDARD



Bead pusher with pulling system



Centering adaptor



Protection



TOP inflation device



Extension and guard

5 models include 1 + 2 + 3

1 PLUS91AKC HELPER

2 INFLATION BY PEDAL

3 G800 A121 WHEEL LIFT

